

Glue for pre-finished parquet PVAc Glue

Special characteristics

Glue for pre-finished parquet used for water-resistant binding. Area of application The pre-finished parquet glue is used for the tongue-and-groove joining of prefinished parquet and flakeboard panels. (The materials must be approved by the manufacturer for floating installation)

Product characteristics

Properties of the liquid adhesive

high-quality, ready-for-use PVAc glue sensitive to frost, solvent-free

Properties after application

resistant to cold water

Color

White

The container can be left open for approx 9 min.

Consumption

pre-finished parquet: approx. 15 g/m flakeboard: approx. 30 g/m

Working climate conditions

Temperature: at least +15 °C

Relative air humidity: 75 %

Packaging

750-g plastic containers

Transportation

never under -20 °C and only once

from -20 °C to 0 °C

Storage

Approx. 12 months in the original, unopened packaging, necessarily protected from frost.

Processing

Apply the liquid glue with a damp cloth. The dry glue must be mechanically removed. Avoid the contact of the liquid glue with metals! Don't use containers made of metal! Use only plastic, glass or ceramic containers. Do not use rusty brushes.

Continuously apply the glue to the lower and upper part of the groove. Tightly press the elements against each other. Remove glue surplus with a damp cloth.

Final instructions

This technical data sheet is based on an extensive experience and is meant to offer you best advice. Restrictions and warnings are included to prevent the risk of error. By their nature, these data sheets cannot consider all the possible uses and all the current and future characteristics, partly due to the great diversity of wood as a material. Therefore, the floor specialist must request information whenever in doubt, perform on-site tests on his own responsibility and perform all operations with extreme care. Furthermore, the data sheet does not provide information assumed to be known by specialists. The content of the data sheet is not legally binding and therefore cannot be taken as a basis for warranty and liability claims. Feel free to contact the WEITZER PARKETT team for any additional questions.



90°

180°