

FEATURE	STANDARD	RESULT
Floor type	EN ISO 10582	Heterogeneous LVT
Installation method	-	For bonding
Total thickness	EN ISO 24346	2.5 mm
Wear layer thickness	EN ISO 24340	0.55 mm
Wear layer thickness Size (length and width)	EN ISO 24342	595 x 150 mm
Acoustic underlay	-	No
Surface protection	-	UV Full Mat
Edge bevelling	-	Synchronous EIR (Embossed In Register)
Packaging (pieces)	-	4-sided
Packaging (square metres)	-	36 pcs/pack
Weight (g/m ²)	-	3.24 m ² / pack
Dimensional stability	EN ISO 23997	4,700 g/m ²
Rectangularity and straightness	EN ISO 23999	< 0.1%
Flexibility	EN ISO 24342	< 0.15 mm
Heat curling Residual indentations	EN ISO 24344	< 20 mm no cracks
Chair on castors	EN ISO 23999	≤ 0.5 mm
Slip resistance	EN ISO 24343-1	0.05 mm
Abrasion class	ISO 4918	resistant (25,000 revolutions)
Dynamic friction coefficient	DIN 51130	R10
Usability class	EN ISO 10582	Group
Flame retardancy class	EN 13893:2004 EN ISO 10874 EN 13501-1	T μ = 0.28 23/33/42
Colour fastness	EN ISO 9239-1	Bfl-s1
Chemical resistance	EN ISO 11925-2	
Electrostaticity	EN ISO 105-B02	
Electrical resistance	EN ISO 26987	> 6
Thermal resistance	EN 1815	Index 0, excellent
Thermal conductivity	EN 1081	≤ 2 kV
Underfloor heating	EN ISO 8302	10 ⁹ Ω
Formaldehyde emission	EN 12667	0.0166 m ² K/W
Pentachlorophenol content	-	0.2841 W/mK
	EN 14041:2004/AC:2006	Max 27°C
	EN 14041:2004/AC:2006	E1
		not found DL PCP

